

TECHNICAL DATASHEET

606050000



FEATURES:

- Universal joint made of anodized aluminium or plastic
- Sealing system with spring makes the device stable and highly adaptable
- 90° flip-up with two clicks
- Version designed for use with safety helmet and ear muffs
- Version available free of exposed metal parts for protection against electric arc (606.04.00.00)

FEATURES FRAME:

Frame Typology	UNIVERSAL JOINT
PPE field of view	>40°
Complete PPE weight (g)	---
Size [mm]	---
Frame Features	Aluminium
Elastic Band Features	---
Ventilation System	---
Spare parts	---

FEATURES OCULARS/LENSES:

Material Ocular/Flip-up	---
Colour	---
Technical Treatment	---
Treatment	---
Thickness [mm] (+/- 0,1)	---
Curvature	---
Optical Class	---
VLT % (+/-5%)	---
UV Protection	---

MARKS:

Standard Reference	EN166 EN175
Frame Marking	U EN166 3 9 AT CE
Frame Marking	U EN175 9 -B CE

FIELDS OF EMPLOYMENT

- A** Protection against high-speed particles 190 m/s - high energy
- T** Protection against high-speed particles at extreme temperatures
- 3** Protection against droplets and splashes of liquids
- 9** Protection against molten metals and hot solids

Notes

